



SUHNER® CORRUGATED COAXIAL CABLE

TYPE: SUCOFEED 1-5/8"

Item: 22511976



Cable design

1	Inner conductor	Helically corrugated copper tube	∅ 17.30 mm
2	Dielectric	Cellular polyethylene (SPE)	∅ 43.00 mm
3	Outer conductor	Corrugated copper tube, welded	∅ 46.50 mm
4	Jacket	Polyethylene (HDPE)	bk (RAL 9005) ∅ 50.00 mm
	Print on jacket	SUHNER SUCOFEED 1-5/8" (Batch no.) (metric length)	

Electrical data

Typ. operating frequency		(GHz)	≤ 2.5
Impedance		(Ω)	50 ± 1
Capacitance		(pF/m)	78.0
Relative signal propagation		(%)	85.5
Signal delay		(ns/m)	3.90
Phase stability	vs temperature	-40 °C ... +70 °C	(ppm)
	vs bending		(°/GHz)
Insulation resistance		(MΩ·m)	> 10 ⁷
Test voltage		50 Hz / 1 min.	(kV _{rms}) 8.0
Max. operating voltage	at sea level		(kV _{rms}) 4.0
Typ. DC resistance	inner conductor		(Ω/km) ≤ 0.70
	outer conductor		(Ω/km) ≤ 0.40
Typ. screening effectiveness			(dB) -

General data

Cable specification	cable design and materials in accordance with	M2939B
Temperature range	operating	(°C) -40...+85
	installation	(°C) -25...+60
Bending moment		(Nm) -
Flame propagation	IEC 332-3	n/a
Halogen content	IEC 754	passed
Typ. Weight		(kg/100m) 150.0
Min. bending radius	for bending once	(mm) 300
	for repeated bendings	(mm) -

Suitable Accessories and Connectors

Accessories	refer to document	03.03.0078
Connector cable group		M42
For details refer to the "SUHNER® coaxial connector catalogue" or contact your nearest HUBER+SUHNER representative		

Document No.: 01.03.2481

Uncontrolled copy

Issue No.: -

Issued/Checked/Released:

08.06.1999/486-HJ

Supersedes: Preliminary issue

Last amended:

Product release


SUHNER® CORRUGATED COAXIAL CABLE

TYPE: SUCOFEED 1-5/8"

Item: 22511976


Cable attenuation

Nominal values @ +25 °C ambient temperature



C.W. power handling capability

Maximum values @ +40 °C ambient temperature and sea level, no solar load



HUBER+SUHNER AG
Coaxial Cable Division
CH-9100 Herisau, Switzerland
Tel.: +41 (0)71 353 41 11
Fax: +41 (0)71 353 45 90
e-mail: sales.hfk@hubersuhner.com
www.hubersuhner.com

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use of purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Document No.: 01.03.2481

Issue No.: -

Supersedes: Preliminary issue

Uncontrolled copy

Issued/Checked/Released:

Last amended:

08.06.1999/486-HJ

Product release